

PA-200RM

16 Zone Remote Microphone

Features:

- ✓ The 16 zone remote microphone for remote announcement use.
- ✓ Paging modes of separate zone, group zone and all zones remote paging.
- ✓ System capacity of 5 remote paging microphones working at the same time.
- ✓ Work together with zone paging controller PA-200PS.
- ✓ Use multiple number buttons to paging more than 320 zones.
- ✓ High sensitivity condenser microphone of chime and mute features.
- ✓ Audio signals using high-quality balanced transmission technology.
- ✓ Audio signals and control signals using real-time transmission technology.
- ✓ External 24V DC input connector.



Specifications:

Model	PA-200RM
Description	16 Zone Remote Microphone
Power Supply	24V DC
Mic. Input	MIC: 600 ohms(Ω) 5mV,unbalanced
Line Output	LINE: 10k ohms(Ω) 10V,unbalanced
Frequency Response	60 Hz ~ 16k Hz (\pm 1 dB)
THD	<0.5% at 1kHz
Power Consumption	<0.25mA
Sensitivity	5mV
Rated Output Level	5V (parallel)
SNR	>70dB
Distortion	<1% (Rated Output), 1KHz
Frequency	100Hz~16KHz
Output Impedance	100 Ω
Operation Temp	+5°C - 40°C
Storage Temp	-20°C - 70°C
Relative Temp	<95%
Dimensions (WxDxH)	238x170x70mm
Net Weight	2.3Kg

Rear Panel:

